



<b>Characteristics</b>	Environmental protection IP40 Faston-terminals Double-break switch Positive-action optional 3mm contact gap
<b>Electrical ratings</b>	400VAC, max. 16A
<b>Range of temperature</b>	-20°C to +140°C
<b>Circuit</b>	CO, NC, NO
<b>Contact material</b>	Silver
<b>Mechanical life</b>	Min. 10 <sup>7</sup> cycles (impact free actuation)
<b>Dimensions</b>	30 x 32 x 12 mm
<b>Actuator</b>	Plunger, plunger with spring, plunger mushroom-head
<b>Approvals</b>	ENEC, UL, cUL, CSA



<b>Characteristics</b>	Environmental protection IP40 Faston-terminals Mechanical intrinsically-safe isolation 8mm contact gap 8mm creepage and clearance distances
<b>Electrical ratings</b>	400VAC, max. 16,5A
<b>Range of temperature</b>	-20°C to +85°C
<b>Circuit</b>	NO
<b>Contact material</b>	Silver-nickel
<b>Mechanical life</b>	Min. 10 <sup>6</sup> cycles (impact free actuation)
<b>Dimensions</b>	40 x 66 x 12,5 mm
<b>Actuator</b>	Plunger, shrouded plunger
<b>Approvals</b>	ENEC, UL, cUL, CSA